

# ISUZU

# FORWARD



**4x2 RIGID**

GVW 11,900kg

**FSR  
PRO**

GVW 16,000kg

**FVR  
PRO**



**FREE  
SERVICE CAMPAIGN**

 **UP TO 100,000km\***  
\*Terms and Conditions apply.

**ISUZU**

**ISUZU  
DOCTOR  
MOBILE**

**24**  
HOUR ASSISTANCE



Reliable support with  
round-the-clock  
business operation.

**1-800-88-8000**

# SPECIFICATIONS

## FSR PRO

## FVR PRO

MODEL CODE	FSR90SU-NC		FVR90SU-SD	
Drive System	4 x 2			
<b>ENGINE</b>				
Model	4HK1-TCS			
Type	4-Cylinder In-line, 4 Cycle, Water-Cooled, OHC, Turbocharger with Intercooler			
Displacement	cc	5,193		
Bore x Stroke	mm	115 x 125		
Maximum Output	kW (PS)@rpm	154 (210) @ 2,600		
Maximum Torque	Nm (kgm)@rpm	637 (65) @ 1,600		706 (72) @ 1,600
Emission Level	Euro 2			
Fuel System	Common Rail Direct Injection			
<b>TRANSMISSION</b>				
Model / No. of Speed	ISUZU MZW6P / 6-Speed Manual			
Gear Ratio	1st	6.615		
	2nd	4.095		
	3rd	2.358		
	4th	1.531		
	5th	1.000		
	6th	0.722		
	Reverse	6.615		
		5.571		6.833
<b>WEIGHT &amp; CAPACITIES</b>				
Gross Vehicle Weight	kg	11,900		16,000
Curb Weight	kg	3,699		5,156
Front	kg	2,242		3,100
Rear	kg	1,457		2,056
Fuel Tank Capacity	l	200		
<b>AXLE</b>				
Front	Type	Reverse Elliot; I Beam		
Front Axle Capacity (Design)	kg	4,100		6,000
Rear	Type	Single Reduction Banjo Design, Full Floating		
Rear Axle Capacity (Design)	kg	7,800		10,500
<b>SUSPENSION SYSTEM</b>				
Suspension	Front	Semi Elliptical Alloy Steel Leaf Springs, Hydraulic Double Acting Telescopic Shock Absorber		
	Rear	Semi Elliptical Alloy Steel Leaf Springs		
<b>TYRES &amp; WHEELS</b>				
Tyres		9R22.5		11R22.5
Wheels		22.5 x 6.75		22.5 x 8.25 (ISO 10 Studs)
<b>BRAKES</b>				
Service		Air Over Hydraulic (AOH), Dual Circuit, Front & Rear Leading Trailing		
Parking Brake Type		Mechanical Expansion Type, Located At The Rear End Of Transmission		
Auxiliary		Exhaust Brake		
<b>STEERING</b>				
Steering System		Power assisted, Hydraulic Integral, Recirculating Ball, Energy absorbing, Tilt & Telescopic Column		
Min. Turning Radius	m	8.29		10.3
<b>ELECTRICAL</b>				
Battery		12V x 2		
Alternator		24V-50A		
<b>DIMENSION</b>				
Overall Length	OAL mm	8,315		10,225
Overall Width	OAW mm	2,200		2,400
Overall Height	OAH mm	2,680		2,805
Wheelbase	WB mm	4,770		6,050
Front Overhang	FOH mm	1,255		1,440
Rear Overhang	ROH mm	2,290		2,735
Front Tread	AW mm	1,795		1,970
Rear Tread	CW mm	1,700		1,850

**ISUZU**

**ISUZU MALAYSIA SDN BHD** 200401026438 (664946-H)


501D, LEVEL 5, TOWER D, UPTOWN 5, NO.5, JALAN SS21/39,  
DAMANSARA UPTOWN, 47400 PETALING JAYA, SELANGOR DARUL EHSAN.  
GENERAL LINE: 03-7723 9777 FAX: 03-7723 9779  
HOTLINE: 1-300-88-1133 www.isuzu.net.my

[IsuzuTrucksMalaysia](#)

**ISUZU SERVICE CENTRE SDN BHD** 201601034731 (1205672-X)

LOT 730, JALAN SG. RASA, SECTION 17,  
40000 SHAH ALAM, SELANGOR DARUL EHSAN.  
PHONE: 03-5513 0518  
FAX: 03-5512 7550

# TESTED AND PROVEN POWERTRAIN



### FVR PRO 4HK1-TCS

Displacement: **5,193cc**  
Max. Output (Gross): **210ps @2,600rpm**  
Max. Torque: **706Nm (72kgm) @1,600rpm**

**210PS**  
MAX POWER

**706Nm**  
MAX TORQUE




### FSR PRO 4HK1-TCS

Displacement: **5,193cc**  
Max. Output (Gross): **210ps @2,600rpm**  
Max. Torque: **637Nm (65kgm) @1,600rpm**


**210PS**  
MAX POWER

**637Nm**  
MAX TORQUE

\*Deeper final ratio 6.833 for better torque startability.




# CLASS-LEADING SAFETY AND LONG TERM COST SAVINGS




Versatile FSR PRO and FVR PRO series cater to a variety of business needs from the 11T to the 16T categories.




New digital meter with enhanced visibility on important information.



Small turning radius for easy maneuvering in congested and tight areas. \*\* Applicable for FSR90SU-NC only



\*Sturdier leaf spring for better driving comfort with heavy loads, and with less deflection.



\*Wide chassis frame 850mm.

\*Applicable for FVR90SU-SD only.

Dealer's information

**ISUZU**  
GENUINE PARTS

**ISUZU**  
BEST VALUE PARTS